

### WOOZEN Color Index



Gray Dark

DC20(Non-slip)

<sup>\*</sup> Colors of the above images can differ from the actual product.





## **Environment-friendly Safety**



#### Woozen is composed of natural and non-toxic material.

• 70% or more natural material wood chip (Wood Fiber) is applied.



### Slip resistance



### Slip resistance

- 19° Angle of inclination
- Greasy condition with Oil





### Composed of natural and non-toxic materials

- Premium product with 70% or more natural material wood chip applied
- Uses non-toxic material, environment-friendly, olefin resin (PE, PP)
- Almost no harmful material generation for safety from skin diseases, etc.



# Strong resistance against heat and moisture, less discoloration and contamination

- Strong resistance against water, so no worry for use of water
- · High dimension stability against heat and moisture
- Strong resistance against mold compared to wood and other synthetic wood



# Various colors and realistic raw wood feeling

- Excellent walking feeling with raw wood texture and surface embossing
- · Presents luxurious interior space
- Same feeling as wood with wood grain embossing application



# Outstanding performance compared to existing products based on technological power

- Wood Fiber is used for strong mechanical strength
- · Not broken even by strong shock
- High abrasion resistance compared to wood and other synthetic wood




## Excellent cost-saving advantages with convenient maintenance

 Dust removal: water cleaning, soft brush, vacuum/steam cleaner can be used

### High quality

# High-quality product with outstanding durability and differentiated technology.

· Lifetime Cost comparison




Clause	WOOZEN	Wood
Annual Expenses	3,960	19,620
Cleaning maintenance	-	5,420
Oil Stain	-	5,200
Maintenance Materials	3,960	9,000

 WOOZEN WFC 20T product presents better quality than its competitor's product WPC 25T product.



· WOOZEN WFC has great dimensional stability.



※ Linear thermal expansion coefficient test value: 5.0X10⁻⁵(1/℃)

#### Sales Subsidiaries & Branches

U.S.A. (Atlanta) TEL: 1-678-486-8244 INDIA (Gurgaon) TEL: 91-124-4212590 RUSSIA (Moscow) TEL: 7-495-663-39-58 EUROPE (Frankfurt) TEL: 0049-69-583029-0 CHINA (Shanghai) TEL: 86-21-5241-6600 CANADA (Toronto) TEL: 1-905-660-4746 TURKEY (Istanbul) TEL: 90-212-285-1101 JAPAN (Tokyo) TEL: 81-3-5299-4533 INDONESIA (Jakarta) TEL: 62-21-2967-5043 VIETNAM (Ho Chi Minh) TEL: 84-28-3915-8909/10 U.A.E. (Dubai) TEL: 971-4-553-1452

### Headquarters

LG Hausys.Ltd One IFC 10 Gukjegeumyung-ro, Yeongdeungpo-gu, Seoul 150-876, Korea