




Specifications

6.0mm(T) X 310mm(W) X 605mm(D)
6.0mm(T) X 150mm(W) X 1220mm(D)

*1) Innovation LG Continous Emboss in Register.





Features & Benefits

- Significant time-saving and easy installation
- Visible and audible locking function to secure installation
- Advanced bristle tongue to overcome production tolerances
- Glass fibre reinforced tongue for outstanding performance

Features

1. Excellent dimensional stability
- Excellent in dimensional stability from low to higher temperatures

2 Excellent anti-Indentation
- Great indentation resistance

3. Non-transfer of floor irregularities
- Strong enough not to transfer floor irregularities

4. No Acclimation
- Strong in dimensional stability even with temperature changes : no acclimation is needed before installation.

5. Sound Reduction
- Reduces noise transfer to rooms below up to 19dB*

* This result is subjected to confirmation in LG Hausys laboratory test.

Sales Subsidiary & Branch

U.S.A. (Atlanta)	TEL : 1-678-486-8244	INDIA (Gurgaon)	TEL : 91-124-4212590
RUSSIA (Moscow)	TEL : 7-495-663-39-58	EUROPE (Frankfurt)	TEL : 0049-69-583029-0
CHINA (Shanghai)	TEL : 86-21-5241-6600	CANADA (Toronto)	TEL : 1-905-660-4746
TURKEY (Istanbul)	TEL : 90-212-285-1101	JAPAN (Tokyo)	TEL : 81-3-5299-4533
INDONESIA (Jakarta)	TEL : 62-21-2967-5043	VIETNAM (Ho Chi Minh)	TEL : 84-28-3915-8909/10
U.A.E. (Dubai)	TEL : 971-4-553-1452		

Headquarters

LG Hausys.Ltd One IFC 10 Gookjegeumyoong-Ro, Yeongdeungpo-Gu, Seoul 150-876, Korea

www.lghausys.com | lginfo@lghausys.com





DecoRigid Color Index


W130D-1


W130D-2


W130D-4


W131D-3


W131D-4


W131D-5


W132D-2


W132D-3


W132D-5


W133D-1


W133D-2


W133D-3


W138D-2


W138D-3


W138D-5

* Colors of the above images can differ from the actual product.


W142-1


W142-2


W142-3


S117D-1


S117D-2


S117D-3


S119S-1



S119S-2


S119S-3


S145-1


S145-2


S145-3


S118D-1


S118D-2


S118D-3